


JST Wire-to-Board Connectors

Potting Type

Series PA High Box

Pitch: 2.0 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 250V AC, DC
 Applicable wire: AWG 28-22
 THT header height: 13.9 mm
 Circuit nos.: 2-15



Series PH High Box

Pitch: 2.0 mm
 Current rating: 2A AC, DC (AWG24)
 Voltage rating: 100V AC, DC
 Applicable wire: AWG 30-24
 THT header height: 15 mm
 Circuit nos.: 2-13



Series PNI

Pitch: 2.0 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 100V AC, DC
 Applicable wire: AWG 28-22
 THT header height: 10.2 mm
 Circuit nos.: 2-10



Series PNI High Box

Pitch: 2.0 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 100V AC, DC
 Applicable wire: AWG 28-22
 THT header height: 16.4 mm
 Circuit nos.: 2-15



Series XH High Box

Pitch: 2.5 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 250V AC, DC
 Applicable wire: AWG 30-22
 THT header height: 14.2 mm
 Circuit nos.: 2-10



Series XA High Box

Pitch: 2.5 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 250V AC, DC
 Applicable wire: AWG 28-22
 THT header height: 17 mm
 Circuit nos.: 2-15



Series VYH

Pitch: 6.5 mm
 Current rating: 15A AC, DC (AWG14/2 circuits)
 Voltage rating: 300V AC, DC
 Applicable wire: AWG 26-14
 THT header height: 15.5 mm
 Circuit nos.: 2-6




Series PID

Pitch: 2.0 mm
 Current rating: 3A AC, DC (AWG 22)
 Voltage rating: 100V AC, DC
 Applicable wire: AWG 26-22
 THT header height: 9.7 mm
 Circuit nos.: 10-30



Series XNI

Pitch: 2.5 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 250V AC, DC
 Applicable wire: AWG 30-22
 THT header height: 10.6 mm
 Circuit nos.: 2-15



Series PXA

Pitch: 2.5 mm
 Current rating: 3A AC, DC (AWG22)
 Voltage rating: 250V AC, DC
 Applicable wire: AWG 26-22
 THT header height: 17 mm
 Circuit nos.: 2, 3 and 6

